



ARDEX WPM 240

Shelter Primer

Solvent Based Primer

For Use With ARDEX Bitumen Systems

Fast Drying

ARDEX Australia Pty Ltd

20 Powers Road
Seven Hills NSW 2147
Phone: 1300 788 780
Fax: 1300 780 102
Email: techinfo@ardexaustralia.com
www.ardexaustralia.com

ARDEX New Zealand Ltd

15 Alfred Street, Onehunga
Auckland, New Zealand 1061
Tel: 0800 227 339
Fax: (03) 384 9779
Email: info@ardexnz.com
www.ardex.co.nz

ARDEX WPM 240

Solvent Based Shelter Primer

PRODUCT DESCRIPTION

ARDEX WPM 240 (Shelter Primer) is a solvent based primer to be used to seal and prepare the substrate prior to the installation of the Shelterbit torch-on and Shelterseal self adhesive membranes.

APPLICATION

Ensure that the surface to be primed is dry and free from dust, oil, paint, curing compounds and any other contaminating materials. Stir contents well before use. Apply by brush, roller or airless spray. ARDEX WPM 240 (Shelter Primer) must be dry before applying membrane.

COVERAGE

1 Litre of ARDEX WPM 240 (Shelter Primer) will cover approximately 5m².

DRYING TIME

Allow 1-2 hours at 23°C.

LIMITATIONS

ARDEX WPM 240 (Shelter Primer) should be used with appropriate mask and breathing apparatus in areas with poor ventilation/air flow.

PACKAGING

5L and 20L

STORAGE

12 Months in the original unopened packaging stored at 23°C.

IDENTIFICATION

ARDEX WPM 240 is available in a Clear and Black liquid.

CLEAN UP

Wash equipment with ARDEX WA98S.

DISCLAIMER The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable New Zealand Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.