



---

# ARDEX WPM 265

**(Water Based Primer)**

---

Creates a positive bond between between the substrate and most ARDEX water based membranes

Can be used on substrates like new and old concrete, timber and compressed fibre boards

---

**ARDEX Australia Pty Ltd**

20 Powers Road  
Seven Hills NSW 2147  
1300 788 780  
technicalservices@ardexaustralia.com  
www.ardexaustralia.com

---

**ARDEX New Zealand Ltd**

15 Alfred Street  
Onehunga, Auckland 1061  
0800 227 339  
info@ardexnz.com  
www.ardex.co.nz

# ARDEX WPM 265

## (Water Based Primer)

### DESCRIPTION

Ardex WPM 265 is a red pigmented, acrylic primer system which creates a positive bond between the substrate and most ARDEX water based membranes. ARDEX WPM 265 can be used in both internal and external applications.

### TYPICAL APPLICATIONS

- New and old concrete.
- Timber.
- Compressed fibreboards.
- Primer for acrylic coatings.

### APPLICATION REQUIREMENTS

#### Substrate preparation

The surface to be coated should be dry, clean, sound and free from oil, grease and flaking paint. New concrete should be left a minimum of 28 days and new render a minimum of 7 days before application commences. All cracks or holes exceeding 2mm are to be repaired before application commences.

#### Application

Apply with brush, long nap roller or conventional spray. Ensure that the coating is applied evenly at the recommended coverage rates. Allow a drying time of at least one hour (at 23°C / 50% R.H.).

#### Can be used with:

- ARDEX WPM 002
- ARDEX WPM 155 Rapid Plus
- ARDEX WPM 310
- ARDEX WPM 130 Builder's Express

### LIMITATIONS

Do not apply ARDEX WPM 265 if the ambient and or substrate temperature is below 10°C or above 35°C. Primed surfaces should preferably be overcoated within the same day of application to avoid intercoat contamination.

### COVERAGE

Approximately 6 m<sup>2</sup>/litre. Coverage rate may vary depending on the porosity of the surface.

### PACKAGING

20L plastic pails.

### CLEAN UP

Clean all equipment in fresh water immediately after use.

### SHELF LIFE

One year in unopened containers stored at 23°C.

### STORAGE

Ardex WPM 265 must be stored above 5°C.

### Pay attention to the following:

Before any substrate preparation, installation or finishing methods relating to ARDEX product are undertaken, please be aware of any potential risks and use appropriate PPE (personal protective equipment). This may involve contacting substrate manufacturers for Safety Data Sheets.

### SAFETY DATA

This product may cause an allergic reaction to the skin. In case of contact with the eyes rinse with running water until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. At times updates can occur to data. For additional information and to ensure you have the most current technical and safety information please consult the latest safety data sheets (SDS) and technical data sheets found on the product page at [www.ardexaustralia.com](http://www.ardexaustralia.com)

### TECHNICAL DATA

VOC content 11g/L

### DISCLAIMER

The technical details, recommendations and other information contained in this datasheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2021. All aforementioned products are the trademarks of ARDEX Australia Ltd, its licensors and affiliates.

This datasheet was issued in March 2021 and is valid for 3 years, in some instances a newer version may be published. Always refer to [www.ardexaustralia.com](http://www.ardexaustralia.com) for the latest technical data from ARDEX Australia Pty Ltd.